

## Product Brochure For S962S

# Hydraulic NC Guillotine - Variable Rake - HG-4008VR

4000 x 8mm Mild Steel Shearing Capacity

1-Axis Ezy-Set NC-89 Go-To Control, Includes Pneumatic Sheet Supports & Hardened Ballscrew Backgauge

**On Sale**

Ex GST

Inc GST

**\$58,500.00**

**\$67,275.00**

**\$57,000.00**

**\$65,550.00**



|  |                             |
|--|-----------------------------|
| ORDER CODE:                                | S962S                       |
| MODEL:                                     | HG-4008VR                   |
| Shearing Capacity - Mild Steel (mm):       | 8                           |
| Shearing Capacity - Stainless Steel (mm):  | 5                           |
| Shearing Length (mm):                      | 4000                        |
| NC Control (Type):                         | Ezy-Set NC-89               |
| Backgauge (Type):                          | Ballscrew                   |
| Backgauge Travel (mm):                     | 1000                        |
| Pneumatic Sheet Supports:                  | Yes                         |
| Quick Action Blade Clearance Adjustment:   | Yes                         |
| Strokes / min (SPM):                       | 10                          |
| Blade Angle (deg):                         | 0° - 2°, Hydraulic Variable |
| Throat Depth (mm):                         | 120                         |
| Motor Power (kW / hp):                     | 7.5 / 10                    |
| Voltage / Amperage (V / amp):              | 415                         |
| Floor Space Requirements (L x W x H) (mm): | -                           |
| Nett Weight (kg):                          | 9700                        |

**METALMASTER**



## Features

- Ezy-Set NC-89 Go-To Programmable digital control provides up to 1000mm travel on hardened ballscrew backgauge allowing operator to program the cut length required. Also fitted is a stroke counter & stroke adjustment dial allowing shorter materials to be cut using a shorter stroke length, this feature will increase production.
- Pneumatic operated material sheet supports mounted to rear of machine. This feature assists in shearing thin material to the correct cut length required simply by preventing thinner material flexing and falling below the backgauge prior to shearing.
- Hydraulic individual sheet material clamping system with nylon inserts to protect material from indentation from the clamping cylinders along full length of machine.
- Adjustable hydraulic variable blade rake system via control panel 0° - 2°
- Control box mounted higher than standard on side of machine to protect it from material damaging the control unit due to heavy material loading on sheet supports prior shearing.
- Simplified blade gap adjustments to allow for a wide range of material types and thicknesses of 0.7 - 8mm enabling minimised distortion of the cut length.
- Transfer balls inserted into work table allowing material to be easily moved to the cut position and squaring arm.
- Top shearing blade made from 6CrW2Si quality composite and has two (2) cutting edges allowing minimised down time in blade rotation.
- Bottom shearing blade made from 6CrW2Si quality composite and has four (4) cutting edges allowing minimised down time in blade rotation.
- The core structure of the steel main frame has been electronically welded ensuring maximum penetration during the manufacturing process. In addition to this feature the cutting beam has been stress relieved eliminating any distortion after manufacturing.
- Shadow line lighting has been incorporated into the machine frame providing a clear cutting line on the work piece and enabling scribed or marked material to be cut with simplicity as required.
- Heavy duty squaring arm is fitted with a graduated rule and adjustable flip up front stops allowing operator to cut to the required size from the front of machine. Flip over stops can be set to repeat cutting length required with accuracy. The arm also aligns the material to be located square to the cutting edge.
- Safety three photo electric rear guards fitted to steel side gates ensuring that the machine will be disabled when person enters rear of machine when in use
- Safety reset button for guarding system located at rear of machine, this feature requires operator to walk to rear of machine to visually check for any obstruction prior to resetting & starting machine
- Mild steel capacity is rated on hot rolled material with 250MPA
- Pre-Commissioning:
  - Guillotine is run & tested prior delivery
  - Hydraulic oil is included with machine

## Includes

- Ezy-Set NC-89 Go-To Programmable hardened ballscrew backgauge 1000mm travel with fine adjustment

## Product Brochure For S962S

- Adjustable hydraulic variable blade rake system via control panel 0° - 2°
- Heavy duty over driven machine construction
- Pneumatic material sheet supports
- Rapid blade gap adjustment
- Emergency stops fitted on both ends of machine for additional safety
- Individual hydraulic hold downs with nylon pads
- Shadow line lighting allows operator to quickly see the cut line
- Swing away backgauge function for cutting long sheets
- 4 edge quality 6CrW2Si blades suitable for stainless steel
- Rexroth & Bosch hydraulic valves
- Telemecanique electrical components
- Transfer balls on table & support arms
- Heavy duty support arms and squaring arms
- Stroke counter and short stroke adjustment
- Sliding chute with ball transfers inserts for cut pieces
- Three safety photo electric light beams on rear guarding

### Specific Features



Right View



Front View




Rear Guarding




3 Safety Electronic Sensors



Safety Omron E3ZS Rear Light Sensor Guarding



Pneumatic Sheet Supports



Motorised Backgauge System



Controller with NC 89



Ezy Set NC 89



Material Transfer Balls



Hand Safety Access



Squaring Arm

Product Brochure For S962S



Adjustable Flip Over Stops




Open Throat for Slitting



Mobile Foot Control




Pneumatic Sheet Support and Emergency Stop on Mobile Foot Control



Machine Lubrication Chart



Cutting Pressure Gauge



Return Pressure Gauge



Variable Blade Gap Adjustment Dial



Rear Guard Reset Button



Fine Adjustment Dial for Backgauge



Emergency Stop Switch



Shown with Optional Ball Transfer Tables - Order Code (L840)

Product Brochure For S962S

**Recommended Accessories**

S960

Hydraulic NC Guillotine -  
Variable Rake

S960S

Hydraulic NC Guillotine -  
Variable Rake

S961

Hydraulic NC Guillotine -  
Variable Rake

S961S

Hydraulic NC Guillotine -  
Variable Rake



M800

Rubber Mat - Anti-Fatigue

M805


Rubber Mat - Anti-Fatigue

O043

Rust & Corrosion Preventive

O042

General Purpose Lubricant &  
Corrosion Inhibitor



## Product Brochure For S962S

---

O044

Rust & Corrosion Preventive

